

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 January 2005 (20.01.2005)


PCT

(10) International Publication Number
WO 2005/005758 A2

- (51) International Patent Classification⁷: E05D
- (21) International Application Number: PCT/US2004/020870
- (22) International Filing Date: 30 June 2004 (30.06.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/483,853 30 June 2003 (30.06.2003) US
- (71) Applicant and
(72) Inventor: BAER, Austin, R. [US/US]; 24416 Highway 550, Ridgway, CO 81432 (US).
- (74) Agents: SPANITZ, Frank, J. et al.; Morgan, Lewis & Bockius LLP, 1111 Pennsylvania Avenue, NW, Washington, DC 20004 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: HINGE WITH STIFFENED LEAF



(57) Abstract: A hinge including a stiffened leaf. The hinge may generally comprise a first longitudinally-extending leaf having a base portion and a mounting portion offset and preferably parallel to the base portion that defines a cavity. The mounting portion may contain at least one hole for attaching the leaf to a hinged object with a fastener. In one embodiment, the hole further includes an annular reinforcement disposed in the cavity proximate to the hole. The hole may be conical in shape and may extend into the reinforcement to receive and support a conically-shaped fastener head. The hinge is suitable for thin leaf construction and continuous full-length hinge applications.



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.